

Electronics Division
Box 1246
1501 Webster Street
Dayton, Ohio 45401
Telephone (513) 223-8161

Operating Instructions

For Model 287ABC SPRINT I ATARI

	SL2			START 2				SR 2			5 V		
LLP	SL1	, x	ST3	LRP	×	×	RLP	CD.	/ x	•••	RRP		
		SL5	0.0			START 1	****	SRI	SR5	SR 3	nnr	ON	OF
×	x	×	×					x	×	x			
		SL4		x .	×	×	x		SR4		. x		
		· x							×				
	SL6		SL7			COIN		SR6		SR7		PO	WER
	, x		×			×		x :		×	×		
			<u> </u>	• •								ÓN	OFF

- 1. Insert the 287B card into the program B connector, number side up.
- 2. Insert the 287A card into the program A connector, number side up.
- 3. Insert the 287C card into the test fixture, number side up.
- 4. Insert the Sprint I game board into the 287C card.
- 5. Connect a speaker to the speaker leads.
- 6. Slide the POWER switch to ON.
- 7. Press COIN or SR-6 to coin the game.
- 8. Press START 1 to start the game.
- 9. SR-5 Steer Right
 SL-5 Steer Left
 SL-6 Gas
 SL-1 1st
 SL-2 2nd
 SL-3 3rd
- 10. Press SR-7 for test.